QD UG MINE

TECHNICAL SPECIFICATION

UNDERGROUND LHD LOADER

UG 2.5 · 5 Ton Diesel Underground LHD Loader

Standard bucket 2.5 m³ · Exported from Qingdao, China



SPECIFICATIONS

Model	UG 2.5 (diesel)
Rated load	5,000 kg
Standard bucket capacity	2.5 m³
Breakout force	103 kN
Traction force	126 kN
Engine	Cummins B5.9, turbocharged, 110 kW / 650 N·m, 6 cylinders
Emission standard	China Stage IV
Transmission	Lingong powershift with torque converter
Drive axle	Meitong CY2F wet-brake axles
Travel speed (F/R)	5.2 / 8.8 / 18.5 / 22.8 km/h (1st–4th)
Steering	±38° steering, 3,050 mm inner radius
Overall dimensions	7,400 × 1,790 × 2,020 mm
Operating weight	14,000 kg
Tire	12.00-24
Cycle time (lift / lower / dump)	5 / 4 / 3 s

Tel: +86 158 9882 2106 **Email:** zang0285@gmail.com **Add:** Licang District, Qingdao, Shandong, China **Web:** ugmine.com

Specifications are subject to change without notice. Contact us for configurations tailored to your mine plan.